Conveyor IIF SERIES





Jitimate Conveyor Entrance












The Industry Leading Carwash Conveyor

from the ground up



The Industry Leading Carwash Conveyor





VPI

1 • ENTRANCE SECTION

- Roller-on-demand
- Removable takeup section
- Direct drive actuator(no linkage system)

- Fork assembly with external rubber pads.
 Steel safety yellow "CAUTION" burnout plate
 Extra-duty "Take-up drum" with UHMW slides
 Stainless Steel take-up drum slide rails (removable)
- Manual control arm R.O.D. assembly (removable)
- Extra-duty 3/4-inch take-up coil spring
- Take-up adjustment capabilities of 10-inches Standard Chain & Roller Wash nozzle

2 • CENTER SECTIONS

- High-strength steel, minimum thickness 3/8-inch
- Three reinforced "H" frames per 10-foot section Durable Painted Sections
- TOP TIER: 5x3x3/8-inch angle Outer guide rail: 2"Dia. x 1/2-inch UHMW plastic tubing Inner guide rail: 1" Round / 2 x 3x 3/8 angle
- MIDDLE TIER: 3 1/2x3 1/2x1/2-inch angle UHMW
- BOTTOM TIER: 5x3x3/8-inch angle
- Yellow safety plate "DO NOT STEP"

3 • EXIT SECTION

- Direct drive hydraulic gear box
- Removable gear box mounting plate
- Heat treated double hub sprocket
- Rubber hinged trap door plate
- Removable exit top plate
- Rubber cushion flap for roller-unit return
- Micro switch structure plate
- Steel safety yellow " CAUTION" burnout plate

4 • CHAIN & ROLLER UNITS

- Single chain operation
- D88k riveted chain or X458
- 1-piece M-2 chain link or M-458 chainlink
- Choice of PECO. 4-wheel roller-units
- Removable idler shaft on all roller-units

U.S.PATENT NO: 4,864,936 / 6,186,073 CANADIAN PATENT NO: 1,322,300

Design Your Conveyor Length Entrance Section: 10' Exit Section: 10' Center Sections: 10' or 5'



CONVEYOR OPTIONS

